

TURCK

Network Media Products

DeviceNet™, minifast® Conduit Adapters


- Gasket and Mounting Screws Provided
- Same Housing Style for Single or Double Port




Housing	Part Number	Specs	Application	Pinout
	BCA 57-M123	Nylon Housing Stainless Steel Receptacle Housing 300 V, 9 A -40° to +75°C	Attaches to standard conduit body* for transition to 5-wire (7/8-16UN) minifast connector *Crouse-Hinds 3/4" Form 8, Mark 9 or equivalent.	<p>Female</p>
	BCA 57-M223		Attaches to standard conduit body* for transition to 5-wire (7/8-16UN) minifast connector *Crouse-Hinds 3/4" Form 8, Mark 9 or equivalent.	

Standard receptacle housing material is stainless steel, for nickel plated brass change part number from ... M223 to ... M224.

1-port Wiring Diagram



2-port Wiring Diagram



DeviceNet™, eurofast® Conduit Adapters


- Gasket and Mounting Screws Provided
- Same Housing Style for Single or Double Port



Housing	Part Number	Specs	Application	Pinout
	BCA 57-E123	Nylon Housing Stainless Steel Receptacle Housing 250 V, 4 A -40° to +75°C	Attaches to standard conduit body* for transition to 5-wire (M12x1) eurofast connector *Crouse-Hinds 3/4" Form 8, Mark 9 or equivalent.	<p>Female</p>
	BCA 57-E223		Attaches to standard conduit body* for transition to 5-wire (M12x1) eurofast connector *Crouse-Hinds 3/4" Form 8, Mark 9 or equivalent.	

Standard receptacle housing material is stainless steel, for nickel plated brass change part number from ... M223 to ... M224.

1-port Wiring Diagram



2-port Wiring Diagram

